

TEMPORARY TRAFFIC CONTROL TYPICAL APPLICATION VEHICLE CONSPICUITY



SIDE VIEW

RED/WHITE SIDE STRIPE IS OPTIONAL FOR
UTILITY COMPANY VEHICLES HAVING
COMPANY SIDE REFLECTIVE STRIPE
MARKINGS MADE FROM MATERIAL SHEETING



BAR LIGHTS MAY BE REPLACED WITH TWO DOME LIGHTS (ONE AMBER FLASHING STROBE AND ONE AMBER FLASHING ROTATING LIGHT SEPARATED BY 36 INCHES MINIMUM).

NOTES:


SPECIFIED BELOW.

- VEHICLE SHALL. ALSO. DISPLAY FLASHING HAZARD/PARKING LIGHTS IN FRONT AND REAR.
- THESE VEHICLE CONSPICUITY REQUIREMENTS SHALL BE MET WHEN VEHICLE STOPS ARE 15 MINUTES MAXIMUM OR LESS, AND AT LOCATIONS WHERE THE LINE OF SIGHT (*) TO VEHICLE WORK ACTIVITY IS ADEQUATE. ALSO, NO ADVANCE SIGNING IS TYPICALLY NEEDED FOR 15 MINUTES OPERATIONS, WHEN THESE VEHICLE CONSPICUITY REQUIREMENTS ARE MET.
- * SEE GENERAL NOTES DEFINITION.

MOBILE OPERATION VEHICLE CONSPICUITY STRIPING/LIGHTING



SIDE VIEW



BACK VIEW

PORTABLE TRAILER VEHICLE CONSPICUITY STRIPING

MATERIAL:

- HIGH PERFORMANCE WIDE ANGLE RETROREFLECTIVE SHEETING-VEHICLE MARKING TAPE

STRIPE WIDTH - 4 INCH MINIMUM

- BAR AND DOME LIGHTS AS APPROVED BY OOT&S

REVISED

REVISED

REVISED



SPECIFICATION 104	CATEGORY CODE ITE	EMS
APPROVED 0	DIRECTOR - OFFICE OF TRAFFIC AND SAFETY	
CNV	APPROVAL • SHA REVISIONS	APPROVAL • FEDERAL HIGHWAY ADMINISTRATION
	APPROVAL 9-10-96	APPROVAL 9-27-96

REVISED

REVISED

10-1-01

Maryland Department of Transportation STATE HIGHWAY ADMINISTRATION

STANDARDS FOR HIGHWAYS AND INCIDENTAL STRUCTURES

GENERAL NOTES

STANDARD NO. MD 104.00-27